






T544

Spring Adjustable Mortised Astragal Set



SEAL

- ▶ Aluminum Alloy 6063, T5 Temper
- ▶ Mortise Dimensions $\frac{9}{16}$ " Wide x $\frac{7}{8}$ "
- ▶ #8 x $\frac{3}{4}$ " Stainless Steel Sheet Metal Screws Furnished





See ngp.com for All Applicable Certifications for this Product.

ngp.com
1-800-NCP-RUSH

INSTALLATION INSTRUCTIONS

144



1. Cut astragal to length.
NOTE Cut from one end, no closer than 1" to the adjusting screw. If necessary to cut more, cut other end.
2. Prepare the door by mortising 7/8" deep x 9/16".
3. Remove gasketing from bar.
4. Remove adjusting screws and inner bar.
5. Position outer case into mortised portion of door.
6. Fasten outer case with screws provided
7. Replace inner bar and adjusting screws.
8. Replace gasketing.
9. Adjust so astragal does not impede proper closing and latching of doors.



ngp.com

1-800-NGP-RUSH

FAX: (800) 255-7874

QUOTES: quotes@ngp.com

ORDERS: orders@ngp.com

MEMPHIS

4985 East Raines Road

Memphis, TN 38118

CARSON CITY

3689 Arrowhead Drive

Carson City, NV 89706