


NCP

T72

Concealed Fastener Perimeter Seal



SEAL



BHMA
CERTIFIED



POSITIVE PRESSURE TESTED GASKETING MATERIALS
FOR FIRE DOORS FOR APPLICATION TO HOLLOW-
METAL-TYPE FIRE DOORS RATED UP TO 3 HOURS
AND WOOD-TYPE FIRE DOORS RATED UP TO 1½
HOURS, CATEGORY H

SILICONE AND NEOPRENE ARE SMOKE
AND DRAFT CONTROL GASKETING
(CATEGORY H) TESTED TO UL 1784;
MEETS REQUIREMENTS OF NFPA 105,
IBC FOR USE ON "S" LABEL DOORS.

- Aluminum Alloy 6063, T5 Temper
- Flame/Moisture Resistant
- #6 X ¾" Stainless Steel Sheet Metal Screws Furnished


ngpp.com

1-800-NCP-RUSH

See ngpp.com for All Applicable
Certifications for this Product.

INSTALLATION INSTRUCTIONS

172



1. Cut seal to fit.
2. With door closed, position seal, mark screw holes.
3. Drill pilot holes for screws using a $\frac{7}{64}$ " drill bit.
4. Install with screws provided in all mounting holes, working from one end to the other.
5. Adjust position so that gasket is slightly compressed against door but does not impede proper closing and latching.



ngp.com

1-800-NGP-RUSH

FAX: (800) 255-7874

QUOTES: quotes@ngp.com

ORDERS: orders@ngp.com

MEMPHIS

4985 East Raines Road
Memphis, TN 38118

CARSON CITY

3689 Arrowhead Drive
Carson City, NV 89706