

The NGP logo consists of the letters "NGP" in a bold, blue, sans-serif font. The letters are contained within a white, shield-like shape with a pointed top and a slightly irregular bottom edge. This white shape is centered on a solid blue rectangular background.

# 402X400 X402

Communicating  
Door  
Threshold



- ▶ Black Vinyl
- ▶ 2 3/4" Wide x 3/4" Tall
- ▶ For Transition Between Two Different Carpets
- ▶ Easy to Install Using Adhesive Like NGP RR5007BL Black RTV Silicone Rubber Construction Sealant
- ▶ Maximum Length = 73"



\* ADA Compliant when installed as illustrated between carpet



POSITIVE PRESSURE TESTED GASKETING MATERIALS FOR FIRE DOORS. FOR APPLICATION TO HOLLOW-METAL-TYPE FIRE DOORS, RATED UP TO 3 HOURS AND WOOD-TYPE FIRE DOORS, RATED UP TO 1-1/2 HOURS. CATEGORY J

**ngp.com**  
1-800-NGP-RUSH

FAX: (800) 255-7874  
QUOTES: quotes@ngp.com

11.24

# THRESHOLD

---

# INSTALLATION INSTRUCTIONS

---




## WARNING:

These products can expose you to chemicals including DEHP Plasticizer, which is known to the State of California to cause cancer and/or developmental and reproductive harm. For more information, go to [P65Warnings.ca.gov](http://P65Warnings.ca.gov).

1. Cut threshold to size required.
2. Notch around door frame if desired.
3. Apply solid beads of adhesive to underside of threshold legs, so when set in place the adhesive spreads to thinly cover base of all legs.

**NOTE:** Adhesive must be a type designed to bond PVC, concrete, wood, metal or other material to which threshold is being applied. NGP black silicone adhesive #RR-5007BL is specifically designed for use to install this threshold.

4. Affix threshold to desired location.



THE PRODUCTS  
YOU COUNT ON  
THE PEOPLE  
YOU TRUST

[ngp.com](http://ngp.com)

FAX: (800) 255-7874

QUOTES: [quotes@ngp.com](mailto:quotes@ngp.com)

ORDERS: [orders@ngp.com](mailto:orders@ngp.com)

### NGP MEMPHIS

4985 East Raines Road  
Memphis, TN 38118

### CARSON CITY

3689 Arrowhead Drive  
Carson City, NV 89706