




INSTALLATION INSTRUCTIONS

600, A605, B606, 672, 675

Astragal Seals



BHMA
CERTIFIED

*See ngp.com for
All Applicable
Certifications for
this Product.*



POSITIVE PRESSURE
TESTED GASKETING
MATERIALS FOR
FIRE DOORS FOR
APPLICATION TO
HOLLOW-METAL-
TYPE FIRE DOORS
RATED UP TO 3
HOURS AND WOOD-
TYPE FIRE DOORS
RATED UP TO
1½ HOURS.
CATEGORY J

ngp.com

1-800-NGP-RUSH

FAX: (800) 255-7874

QUOTES: quotes@ngp.com

ORDERS: orders@ngp.com



INSTALLATION INSTRUCTIONS

600, A605, B606, 672, 675

1. Remove brush from metal retainer.
2. Cut brush to length, using the cutting section of pliers or diagonal cutters. If bristles are not secure, use a drop of adhesive to secure the brush.
3. Cut the metal retainer to length.
4. Replace brush in metal retainer.
5. Position on door as shown above.
6. Mark screw holes.
7. Drill pilot holes with a $\frac{7}{64}$ " bit.
8. Install with screws provided.
9. Slightly peen the bottom end of each retainer in order to secure the brush from moving.
10. Adjust astragal so it does not impede proper closing and latching of the doors.



ngp.com
1-800-NGP-RUSH

FAX: (800) 255-7874
QUOTES: quotes@ngp.com
ORDERS: orders@ngp.com

NGP MEMPHIS

4985 East Raines Road
Memphis, TN 38118

CARSON CITY

3689 Arrowhead Drive
Carson City, NV 89706