# 8145

Custom Fabricated
Threshold Component

- Aluminum Alloy 6063, T5 Temper
- 5" Wide x ¼" Tall
- BHMA Certified to ANSI/BHMA A156.21 1,000 Lb. Load Test
- Weight: 1.20 Lbs./Ft.
- #10 FH Zinc Plated Wood Screws Included

# THRESHOLD

BHMA CERTIFIED

UL CERTIFIED SAFETY IUS-CA R10042

POSITIVE PRESSURE TESTED GASKETING MATERIALS FOR FIRE DOORS. FOR APPLICATION TO HOLLOW-METAL-TYPE FIRE DOORS, RATED UP TO 3 HOURS AND WOOD-TYPE FIRE DOORS, RATED UP TO 1½ HOURS. CATEGORY J

**ngp.com**
**1-800-NGP-RUSH**

FAX: (800) 255-7874
QUOTES: quotes@ngp.com

10.24

# INSTALLATION INSTRUCTIONS

1. Cut threshold to size required.
2. Notch around door frame if desired.
3. Attach to floor surface with fasteners provided.
4. Caulk around base of threshold for moisture control.

NGP

THE PRODUCTS
YOU COUNT ON
THE PEOPLE
YOU TRUST

ngp.com

FAX: (800) 255-7874
QUOTES: quotes@ngp.com
ORDERS: orders@ngp.com

**NGP MEMPHIS**
4985 East Raines Road
Memphis, TN 38118

**CARSON CITY**
3689 Arrowhead Drive
Carson City, NV 89706