

The NGP logo consists of the letters "NGP" in a bold, blue, sans-serif font. The letters are contained within a white, shield-like shape with a pointed top and bottom. This shield is centered on a solid blue rectangular background.

8150

Custom Fabricated Threshold Component



- ▶ Aluminum Alloy 6063, T5 Temper
- ▶ 10" Wide x 1/4" Tall
- ▶ Weight: 2.40 Lbs./Ft.
- ▶ #10 FH Zinc Plated Wood Screws Included



BHMA
CERTIFIED



POSITIVE PRESSURE TESTED GASKETING MATERIALS FOR FIRE DOORS. FOR APPLICATION TO HOLLOW-METAL-TYPE FIRE DOORS, RATED UP TO 3 HOURS AND WOOD-TYPE FIRE DOORS, RATED UP TO 1½ HOURS. CATEGORY J

THRESHOLD

ngp.com
1-800-NGP-RUSH

FAX: (800) 255-7874
QUOTES: quotes@ngp.com

INSTALLATION INSTRUCTIONS

1. Cut threshold to size required.
2. Notch around door frame if desired.
3. Attach to floor surface with fasteners provided.
4. Caulk around base of threshold for moisture control.



NGP

THE PRODUCTS
YOU COUNT ON
THE PEOPLE
YOU TRUST

ngp.com

FAX: (800) 255-7874
QUOTES: quotes@ngp.com
ORDERS: orders@ngp.com

NGP MEMPHIS
4985 East Raines Road
Memphis, TN 38118

CARSON CITY
3689 Arrowhead Drive
Carson City, NV 89706