

The NGP logo consists of the letters "NGP" in a bold, blue, sans-serif font. The letters are contained within a white, shield-shaped outline with a pointed top and a pointed bottom. The entire logo is centered on a solid blue rectangular background.

# 8163

## Custom Fabricated Threshold Component



- ▶ Aluminum Alloy 6063, T5 Temper
- ▶ 3" Wide x 1/2" Tall
- ▶ Weight: .75 Lbs./Ft.
- ▶ #10 FH Zinc Plated Wood Screws Included



POSITIVE PRESSURE TESTED GASKETING MATERIALS FOR FIRE DOORS. FOR APPLICATION TO HOLLOW-METAL-TYPE FIRE DOORS, RATED UP TO 3 HOURS AND WOOD-TYPE FIRE DOORS, RATED UP TO 1½ HOURS. CATEGORY J

# THRESHOLD

[ngp.com](http://ngp.com)  
1-800-NGP-RUSH

FAX: (800) 255-7874  
QUOTES: [quotes@ngp.com](mailto:quotes@ngp.com)

---

# INSTALLATION INSTRUCTIONS

---

1. Cut threshold to size required.
2. Notch around door frame if desired.
3. Attach to floor surface with fasteners provided.
4. Caulk around base of threshold for moisture control.



THE PRODUCTS  
**YOU COUNT ON**  
THE PEOPLE  
**YOU TRUST**

[ngp.com](http://ngp.com)

FAX: (800) 255-7874  
QUOTES: [quotes@ngp.com](mailto:quotes@ngp.com)  
ORDERS: [orders@ngp.com](mailto:orders@ngp.com)

**NGP MEMPHIS**  
4985 East Raines Road  
Memphis, TN 38118

**CARSON CITY**  
3689 Arrowhead Drive  
Carson City, NV 89706