



NGP

8427

Thermal Break
Saddle Threshold
 $\frac{1}{2}$ " x $7\frac{1}{8}$ "



- ▶ Aluminum Alloy
6063, T5 Temper
- ▶ $7\frac{1}{8}$ " Wide x $\frac{1}{2}$ " Tall
- ▶ Fluted Top
- ▶ Typical Wall
Thickness: .110"
- ▶ Weight: 1.20 Lbs./Ft.
- ▶ #10 x $1\frac{1}{2}$ " FH Zinc
Plated Wood Screws
Included



THRESHOLD

ngp.com
1-800-NGP-RUSH

FAX: (800) 255-7874
QUOTES: quotes@ngp.com

8.24

INSTALLATION INSTRUCTIONS

1. Cut threshold to size required.
2. Notch around door frame if desired.
3. Attach to floor surface with fasteners provided.
4. Caulk around base of threshold for moisture control.



THE PRODUCTS
YOU COUNT ON
THE PEOPLE
YOU TRUST

ngp.com

FAX: (800) 255-7874
QUOTES: quotes@ngp.com
ORDERS: orders@ngp.com

NGP MEMPHIS
4985 East Raines Road
Memphis, TN 38118

CARSON CITY
3689 Arrowhead Drive
Carson City, NV 89706