




NGP

8533

Aluminum
Thermal Break Bumper
Seal Threshold
 $\frac{1}{2}$ " x $5\frac{1}{8}$ "



- ▶ Aluminum Alloy 6063, T5 Temper
- ▶ $5\frac{1}{8}$ " Wide x $\frac{1}{2}$ " Tall
- ▶ Fluted Top
- ▶ Weight: .83 Lbs./Ft.
- ▶ #10 x $1\frac{1}{2}$ " FH Zinc Plated Wood Screws Included. Dark Bronze Supplied with DKB Thresholds



THRESHOLD


ngp.com
1-800-NGP-RUSH

FAX: (800) 255-7874
QUOTES: quotes@ngp.com

11.24

INSTALLATION INSTRUCTIONS

1. Cut threshold to size required.
2. Notch around door frame if desired.
3. Attach to floor surface with fasteners provided.
4. Caulk around base of threshold for moisture control.



NGP

THE PRODUCTS
YOU COUNT ON
THE PEOPLE
YOU TRUST
ngp.com

FAX: (800) 255-7874
QUOTES: quotes@ngp.com
ORDERS: orders@ngp.com

NGP MEMPHIS
4985 East Raines Road
Memphis, TN 38118

CARSON CITY
3689 Arrowhead Drive
Carson City, NV 89706