



# NGP

# 8813

Thermal Break  
Saddle Threshold  
 $\frac{1}{4}$ " x  $8\frac{1}{8}$ "



- ▶ Aluminum Alloy  
6063, T5 Temper
- ▶  $8\frac{1}{8}$ " Wide x  $\frac{1}{4}$ " Tall
- ▶ Fluted Top
- ▶ Typical Wall  
Thickness: .125"
- ▶ Weight: 1.11 Lbs./Ft.
- ▶ #10 x  $1\frac{1}{2}$ " FH Zinc  
Plated Wood Screws  
Included



# THRESHOLD

**ngp.com**  
1-800-NGP-RUSH

FAX: (800) 255-7874  
QUOTES: quotes@ngp.com

8.24

---

# INSTALLATION INSTRUCTIONS

---

1. Cut threshold to size required.
2. Notch around door frame if desired.
3. Attach to floor surface with fasteners provided.
4. Caulk around base of threshold for moisture control.



**NGP**

THE PRODUCTS  
**YOU COUNT ON**  
THE PEOPLE  
**YOU TRUST**

[ngp.com](http://ngp.com)

FAX: (800) 255-7874  
QUOTES: [quotes@ngp.com](mailto:quotes@ngp.com)  
ORDERS: [orders@ngp.com](mailto:orders@ngp.com)

**NGP MEMPHIS**  
4985 East Raines Road  
Memphis, TN 38118

**CARSON CITY**  
3689 Arrowhead Drive  
Carson City, NV 89706