



The NGP logo consists of the letters "NGP" in a bold, blue, sans-serif font. The letters are contained within a white, shield-shaped border with a slightly irregular, hand-drawn appearance. This shield is centered on a solid blue rectangular background.

884B/S

Extended Width
Threshold Component
2 x 7/8"



- ▶ Aluminum Alloy
6063, T5 Temper
- ▶ 2" Wide x 7/8" Tall
- ▶ Typical Wall
Thickness: .110"
- ▶ Weight: .48 Lbs./Ft.
- ▶ #10 x 1 1/2" FH Zinc
Plated Wood Screws
Included

 (V) Vinyl Bumper Seal Standard
Optional: (N) NGP-TPV
(S) Silicone




THRESHOLD

ngp.com
1-800-NGP-RUSH

FAX: (800) 255-7874
QUOTES: quotes@ngp.com

INSTALLATION INSTRUCTIONS

1. Cut threshold to size required.
2. Notch around door frame if desired.
3. Attach to floor surface with fasteners provided.
4. Caulk around base of threshold for moisture control.



THE PRODUCTS
YOU COUNT ON
THE PEOPLE
YOU TRUST
ngp.com

FAX: (800) 255-7874
QUOTES: quotes@ngp.com
ORDERS: orders@ngp.com

NGP MEMPHIS
4985 East Raines Road
Memphis, TN 38118

CARSON CITY
3689 Arrowhead Drive
Carson City, NV 89706