




# 955

## ADA Compliant Interlocking Ramp 3" Wide x 1 1/4" Tall



- ▶ Aluminum Alloy 6063, T5 Temper
- ▶ 3" Wide x 1 1/4" Tall
- ▶ BHMA Certified to ANSI/BHMA A156.21  
1,000 Lb. Load Test
- ▶ Typical Wall Thickness: .110"
- ▶ Weight: .71 Lbs./Ft.
- ▶ #10 FH Zinc Plated Wood Screws Included



POSITIVE PRESSURE TESTED GASKETING MATERIALS FOR FIRE DOORS. FOR APPLICATION TO HOLLOW-METAL-TYPE FIRE DOORS, RATED UP TO 3 HOURS AND WOOD-TYPE FIRE DOORS, RATED UP TO 1 1/2 HOURS. CATEGORY J



*\*When Installed as Part of an Interlocking Ramp Assembly.*

**ngp.com**  
**1-800-NGP-RUSH**

FAX: (800) 255-7874  
QUOTES: QUOTES@NGP.COM  
ORDERS: ORDERS@NGP.COM


# THRESHOLD

---

# INSTALLATION INSTRUCTIONS

---

1. Assemble ramp by interlocking sections together.
2. Cut ramp to fit.
3. Position return closed end (if ordered) on each side of ramp.
4. Drill and counter sink screw holes in ramp aligned with holes in RCE.
5. Install ramp with screws provided.
6. Caulk around base of ramp and RCE for moisture control.



**NGP MEMPHIS**  
4985 East Raines Road  
Memphis, TN 38118

FAX: (800) 255-7874  
QUOTES: [quotes@ngp.com](mailto:quotes@ngp.com)  
ORDERS: [orders@ngp.com](mailto:orders@ngp.com)

**CARSON CITY**  
3689 Arrowhead Drive  
Carson City, NV 89706

