9590-2

Fire Door Bottom Gap Solution — *Up To 180 Minutes*

PRODUCT CUT SHEET

PROJECT:	
SUBMITTED BY:	
DATE:	
NOTES:	

UL Certified for Door Bottom Gaps — Measuring up to 2"

UL CERTIFIED FOR USE IN THE US AND CANADA

- 180-Minute Rated on Hollow Metal Doors, 90-Minute Rated on Wood Doors
- For Use on UL10B and UL10C Wood or Hollow Metal Fire Doors
- Restricts the Passage of Smoke
- Available in 36" and 48" Lengths
- Non-Handed
- Patented: US Patent US 11,873,679 B2

PRODUCT CONSISTS OF:

+ #304 Brushed Stainless Steel Neoprene Sweep — Pull Side
+ #304 Brushed Stainless Steel Intumescent Shoe — Push Side
+ #304 Brushed Stainless Steel End Caps
+ #6 X ¾" Stainless Steel SMS Furnished

FINISH:

Brushed Stainless Steel
Neoprene is Black



NGP-GAP-9590-PCS-0726-A

NATIONAL GUARD PRODUCTS, INC.

MEMPHIS
4985 East Raines Road
Memphis, TN 38118

CARSON CITY
3689 Arrowhead Drive
Carson City, NV 89706

Fax: (800) 255-7874
Email: info@ngp.com

Quotes: quotes@ngp.com
Orders: orders@ngp.com

ngp.com
1-800-NGP-RUSH