

# ELECTRIC THRU-WIRE

## ETW8

### Eight Wire Electric Thru-Wire

Transfers Electric Power Through the Hinge to Power Certain Types of Electronic Builders Hardware.


#### REMOVABLE ELECTRIC HINGE SECTION

- ▶ 8 Wires, 28 AWG
- ▶ Each Wire is Rated 50V AC/DC at 3.5A (max.) Continuous, or 16A (max.) Pulse; Maximum Pulse Width is 400 msec with 10 Second Minimum Off Time Between Pulses
- ▶ 12" Minimum Wire Leads
- ▶ 5-year Warranty

## ETW8 - MOLEX

### Eight Wire Electric Thru-Wire with Molex Connectors

- ▶ Same Features as Above with Molex Connectors Installed on Wires Both Sides



#### Available on Models

HD1100  
HD2400 (Handed)  
HD2700



#### STANDARD LOCATIONS

HINGE LENGTH	TOP OF HINGE TO CENTERLINE
83"	40 1/2"
85"	42 1/2"
95"	52 1/2"
119"	76 1/2"

All sizes located 42 1/2" centerline from bottom of hinge

#### DRILL 3/4" HOLE IN FRAME AND DOOR TO ACCEPT WIRES FOR ETW8 & ETW12

