

GAP90

FIRE DOOR HEAD AND JAMB GAP SOLUTION



UL CERTIFIED FOR USE IN
THE US AND CANADA

- ▶ **UL Certified Solution for 60 and 90 Minute Fire Doors with Excessive Clearance**
Between Door and Frame Over $\frac{1}{8}$ " up to $\frac{3}{8}$ ".
- ▶ **UL Certified Solution for 20 and 45 Minute Fire Doors with Excessive Clearance**
Between Door and Frame Over $\frac{1}{8}$ " up to $\frac{9}{16}$ ".

INSTALLED
VIEW

PRODUCT CONSISTS OF:

9945

Steel Stop Extender

- ▶ 16-Gauge, Gray Primer Finish
- ▶ Furnished with #10 X 1" TEK SMS
- ▶ Embossed with **UL Mark**
- ▶ Patented: US Patent 9,273,510 B2

5075

Self-Adhesive Silicone Seal

5075C CHARCOAL

5075CL CLEAR






9400

NGP-Edge® Intumescent Seal with PVC Cover

9400GR GRAY

9400C CHARCOAL



POSITIVE PRESSURE TESTED
MISCELLANEOUS FIRE DOOR
ACCESSORY

90-Minute Rated UL Certified Miscellaneous Fire Door Accessory on UL10B and UL10C Wood or Hollow Metal Fire Doors.

An NGP Strike Shim 9275 or 9225 may also be Required for Proper Latchbolt Engagement.

Doors with Parallel Arm Closers — Use 9990 Fire Door Top Gap Solution.

GAP90 INCLUDES 9945, 9400GR, 5075CL

GAP90DKB INCLUDES 9945, 9400C, 5075C

Available in 36", 48", 84" and 96" Lengths