



# L-CVFM-316SS-SP

Stainless Steel Lite Kit

## PRODUCT CUT SHEET

### For Variable Door and/or Glass Thickness

- 18 Ga. Type 316 Stainless Steel
- Mitered and Welded Corners
- Welded Reinforcing Clips at Corners
- Counter-Sunk Mounting Screw-Holes
- Available in Uneven and Fractional Sizes
- #8 Phillips Head SMS
- #4 Satin Finish

### Required Information

- Specify Glass Thickness on Order
- Specify Door Thickness on Order if Other Than 1 3/4"

### Available Options

- Torx Security Screws
- Glass & Glazing Tape
- Lead Lining - 1/16" Thick



PROJECT:

SUBMITTED BY:

DATE:

NOTES:

- Details Shown are for 1 3/4" Door Thickness
- Only Configurations Shown are Available
- \*Requires the Use of GT-316 Glazing Tape

	DOOR	GLASS	GL. TAPE
	1-3/4"	3/8"	GT-114
	1-3/4"	7/16"	GT-114
	1-3/4"	1/2"	GT-316
	1-3/4"	9/16"	GT-118
	1-3/4"	5/8"	GT-118
	1-3/8"	1/4"	GT-118
	1-3/4"	3/4"	GT-114
	1-3/4"	7/8"	GT-316
	1-3/4"	1"	GT-118
	1-3/8"	3/8"	GT-114
	1-3/8"	1/2"	GT-316

Designed for Use on 1 3/4" Thick Doors Manufactured Within Door Industry Tolerance of +/- 1/16".

NGP-LIT-L-CVFM-316SS-SP-PCS-0323-A

**NGP MEMPHIS**  
4985 East Raines Road  
Memphis, TN 38118  
orders@ngp.com

**NGP VEGAS**  
4584 Calimesa Street  
Las Vegas, NV 89115  
vegasorders@ngp.com

**ngp.com**  
1-800-NGP-RUSH