



# L-SG100-TB

## Thru-Bolted Security Grille Lite Kit

### PRODUCT CUT SHEET

#### For 1 3/4" Thick Doors and Variable Glass Thickness

- 18 Ga. Cold Rolled Steel
- 16 Ga. Steel 3/4" x 3/4" Security Grille Welded in Both Sides
- Mitered and Welded Corners
- Welded Reinforcing Clips at Corners
- Countersunk Mounting Screw-Holes
- Thru-Bolts for 1 3/4" Door
- Gray Primer (GPZ) Powder Coat Finish

#### Required Information



- Specify Glass Thickness on Order

#### Available Options

- Powder Coat Color Options - See Color Chart on [ngp.com](http://ngp.com)
- False Mullion Bars
- Torx Security Thru-Bolts
- Galvanneal - A40 Steel
- Zinc Electro-Plating
- Glass & Glazing Tape
- Lead Lining - 1/16" Thick



\*up to 90 minutes



PROJECT:

SUBMITTED BY:

DATE:

NOTES:

- Details Shown are for 1 3/4" Door Thickness
- Only Configurations Shown are Available
- Thru-Bolts Available for 1 3/4" Thick Doors Only

DOOR	GLASS	GL. TAPE	
1-3/4"	1/8"	GT-118	
2"	3/8"	GT-118	
2-1/4"	5/8"	GT-118	
1-3/4"	3/16"	GT-114	
1-3/4"	1/4"	GT-114	
1-3/4"	5/16"	GT-114	
1-3/4"	1/2"	GT-118	
1-3/4"	2"	3/4"	GT-118
1-3/4"	5/8"	GT-118	
1-3/4"	3/4"	GT-316	
1-3/4"	7/8"	GT-118	
1-3/4"	1"	GT-118	
1-3/4"	1-1/8"	GT-118	
1"	3/8"	GT-118	

Designed for Use on 1 3/4" Thick Doors Manufactured Within Door Industry Tolerance of +/- 1/16".

NGP-LIT-L-SG100-TB-PCS-0323-B

**NGP MEMPHIS**  
4985 East Raines Road  
Memphis, TN 38118  
[orders@ngp.com](mailto:orders@ngp.com)

**NGP VEGAS**  
4584 Calimesa Street  
Las Vegas, NV 89115  
[vegasorders@ngp.com](mailto:vegasorders@ngp.com)

**ngp.com**  
1-800-NGP-RUSH